

*By [Signature]*  
said corrugated fin, and a width of said tubes is smaller than said width of said corrugated fin.

---

**REMARKS**

Applicants appreciate the hospitality of the examiner in conducting an interview on September 6, 2001. The foregoing amendments to claims 1 and 5 are a result of the interview with the examiner in which arguments and amendments for overcoming the cited references was discussed. Applicants believe that claims 1 and 5 (and their dependent claims) are in condition for allowance.

*respect* ( In addition, as for claim 9, Applicants respectfully believe that this claim is clearly a method of manufacture claim, and should be treated as such by the Patent Office.

In short, Applicant respectfully asserts that the presently pending claims are patentable over the cited art.

**CONCLUSION**

In view of the foregoing, it is respectfully urged that the present claims are in condition for allowance. An early notice to this effect is earnestly solicited. Should there be any questions regarding this application, the Examiner is invited to contact the undersigned at the number shown below.

September 24, 2001

Date

Respectfully submitted,

*[Signature]*

Pavan K. Agarwal

Reg. No. 40,888

FOLEY & LARDNER  
Suite 500, 3000 K Street, N.W.  
Washington, D.C. 20007-5109  
Phone: (202) 672-5300  
Fax: (202) 672-5399

**THE COMMISSIONER IS HEREBY AUTHORIZED TO CHARGE ANY DEFICIENCY OR CREDIT ANY OVERPAYMENT TO DEPOSIT ACCOUNT NO. 19-0741.**

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

1. (Twice Amended) A heat exchanger core comprising:

a pair of header members being spaced with a predetermined clearance therebetween and disposed opposite to each other;

tubes and corrugated fins which are interposed between said pair of header members and are arranged alternately; and

a reinforcement member being provided on ends of said mutually-opposing header members,

wherein each of said header members has tube holes into which ends of said tubes are fixedly inserted and reinforcement holes into which ends of said reinforcement members are fixedly inserted,

wherein each of said reinforcement holes is formed so as to be of the same size as or larger than each of said tube holes, and

wherein an interval between said reinforcement hole and said tube hole adjacent to said reinforcement hole is made equal to an interval between adjacent tube holes,

wherein said reinforcement hole comprises <sup>11b</sup>continuous <sup>11c</sup>circular-arch sections being formed at both ends thereof in a thickness direction and a linear section being formed between said circular-arch sections, and

wherein an <sup>11a</sup>insertion section is formed at an end of said reinforcement member so as to have [a] an end face being rectangular in cross section and be fixedly inserted into said <sup>11b</sup>reinforcement hole, and <sup>11c</sup>a width of said insertion section is made smaller than a <sup>11d</sup>width of said reinforcement hole as well as larger than a length of the linear section so that said insertion section is inserted into said reinforcement hole by press-fitting.

5. (Amended) A heat exchanger core comprising:

a pair of header members being spaced with a predetermined clearance therebetween and disposed opposite to each other; and

tubes and corrugated fins which are interposed between said pair of header members and are arranged alternately,

a reinforcement member being provided on ends of said mutually-opposing header members,

wherein each of header members has tube holes into which ends of said tubes are fixedly inserted and reinforcement holes into which ends of said reinforcement members are fixedly inserted, said reinforcement member comprises a reinforcing section having a C-shaped cross section and insertion sections which are integrally formed with opposite ends of said reinforcing section, [and] a width of said reinforcement member is smaller than a width of said corrugated fin, and a width of said tubes is smaller than said width of said corrugated fin.